



NadieMeLlamaGallina.com

Porque Yo Lo Reparo

Step by step tutorial: of Motorola Google Nexus 6 Audio connector

For this tutorial you will need the following spared parts and tools that you cant get at our online store Impextrom.com
Click on a tool for visit the website.



Kit of tools
profesional 70 in 1 -
ARTICLE NUMBER:
LSP031634

16,67 €

Step 1 - Motorola Nexus 6

Motorola Google Nexus 6

Physical dimensions: 82.98 x 159.26 mm, 10 millimeters thick, 184 grams

Screen: AMOLED of 5.96 inches, Resolution 2560x1440, 493 ppp

Processor: Qualcomm® Snapdragon™ 805 4-core 2.7GHz

Graphic processor: Adreno 420

RAM: 3 GB

Memory: 32/64 GB (not microSD)

OS: Android 5.0 Lollipop

Connectivity: WiFi 802.11ac 2x2 (MIMO), Bluetooth 4.1, LTE / NFC

Rear camera: 13 Megapixels with Dual Led Flash

1 / 3.06 ", f / 2.0, 28mm

Optical stabilization, HDR +, 4K Video

Front camera: 2 megapixels

Battery: 3,220 mAh

Before starting, make sure that the equipment is turned off.



Step 2 - SIM tray

Remove the SIM tray.



Step 3 - Back cover

In this model we find that the back cover is fixed with adhesive. To detach it, we introduce the tip of a pick and go around the contour.





Step 4

Holding the lid with a suction cup, we separate the lid by one of the sides, just enough to insert a flat plastic tool, which allows us to take off the center of the lid.

As you can see in the photographs, the adhesive occupies almost the entire surface. It is recommended to replace it before reinstalling the cover.





Step 5 - Intermediate housing

Remove the 22 Torx screws that hold the back cover.



Step 6

Remove the plastic cover and disconnect the flex from the battery.





Step 7

Use the prong to release the plastic hooks located on the contour of the housing.





Step 8 - Audio connector

Finally, take off the audio connector. You can push it with a pointed tool or use the spatula for it.

