



**NadieMeLlamaGallina.com**

Porque Yo Lo Reparo


## Step by step tutorial: of Wiko Sunny 2 Motherboard

For this tutorial you will need the following spared parts and tools that you cant get at our online store [Impextrom.com](http://Impextrom.com)  
Click on a tool for visit the website.




Double SMD  
soldering station,  
Baku 878

59,85 €



Professional  
disassembly spatula  
for mobile phones  
and smartphones

2,71 €




Opening tool  
Smartphone, tablet

2,19 €




Pinza antiestática  
ESD redondeada

3,06 €



Set of professional  
tools for opening  
smartphones and  
tablets

18,97 €



Screwdriver phillips  
Head Size 00

1,06 €



Touch ESD glove, for  
antistatic protection,  
size M

4,16 €



Antistatic and ESD  
tactile glove, size S

5,30 €

### Step 1 - Remove back casing

We start by removing the back cover. To do this we introduce a tool between it and the frame and slide it around the contour to unhook it. We can also do it directly with our hands.





## Step 2 - Remove battery

Disengage the battery by prying it with a tool or with your hands.





### Step 3 - Intermediate housing

We remove the six Phillips screws (PH # 0) that hold the intermediate housing and unhook it by prying it with an opening tool. To be able to remove it, we will have to take off the adhesive that covers the motherboard.







#### Step 4 - Unseal screen

Now we take off the flex of side push buttons and disengage the display to be able to separate the touch screen.





## Step 5 - Motherboard

To finish, take off the LCD panel display, sliding a flat tool along the sides of it. We will also take off the adhesive that has in the back part to be able to separate it.

Now, to finish, we will desolder the components of the motherboard.





