



NadieMeLlamaGallina.com

Porque Yo Lo Reparo

Step by step tutorial: of ZTE Blade V8 Auxiliary plate

For this tutorial you will need the following spared parts and tools that you cant get at our online store Impextrom.com
Click on a tool for visit the website.



SIM card removal
tool for all brands

1,61 €



Opening tool
Smartphone, tablet

2,19 €



Pinza antiestática
ESD redondeada

3,06 €




Special SAT 0.75mm
high friction PVC pick

1,07 €



6-in-1 screwdriver, K-
8107 with different
heads, in blister

7,52 €



Auxiliary plate with
connector charger,
data and accessories
Micro USB for ZTE

3,76 €

Step 1 - Screws

To begin with we will remove the two Pentalobe screws (TS1).



Step 2 - Tray

We extract the tray of the cards with the help of the extraction tool.



Step 3 - Back case

With the help of one or more barbs, we uncouple the entire side of the casing.



Step 4 - Antenna module with loudspeaker

We extract the four Phillips screws (PH # 00) that hold the loudspeaker, and with the help of an opening tool we will disengage the loudspeaker antenna module.



Step 5 - Auxiliary plate

Disconnect the coaxial cable, disconnect the flex from the front button, the interconnection flex that is connected to the underside of the auxiliary plate and we can remove the plate.



